



WINDOW FILM PERFORMANCE DATA

Automotive and Architectural: Philippines

	% Visible Light Transmission	% Total Solar Energy Rejection	% Ultraviolet Protection	% Visible Light Reflection
ATR Series (High-Performanced Metallized Tinted Window Tint) Long-lasting looks plus superior heat rejection				
ATR 05 CH SR HPR (Charcoal)	5	63	>99	8
ATR 15 CH SR HPR (Charcoal)	15	50	>99	8
ATR 20 BR SR HPR (Bronze)	23	48	>99	8
ATR 35 CH SR HPR (Charcoal)	38	44	>99	8
AIR Series (Clear Window Tint) Lightly-shaded tint that reduces heat but not visibility				
AIR 65 GN SR HPR (Clear Green)	63	44	>99	8
AIR 75 SR HPR (Clear)	73	39	>99	9
AIR 80 BL SR HPR (Clear Blue)	78	43	>99	9
REFLECTIVE Series (Solar Control Window Film) Providing a high level of glare and heat control				
LR 20 SI SR HPR (Silver)	18	77	99	60
R 15 GN SR HPR (Green)	15	75	99	32
R 15 BL SR HPR (Blue)	11	75	99	25
RN 07 G SR HPR (One-way Mirror)	5	84	99	60
N 1020 SR CDF (Dark Neutral)	24	63	99	29
N 1040 SR CDF (Medium Neutral)	40	50	99	18
N 1050 SR CDF (Light Neutral)	49	42	99	14
DECO Series (Decorative Window Film) Ideal interior glazing applicatins to achieve privacy or interior design goals				
NRM PS2 (Frosted)	75	27	98	25
NRM FBS HPR (Bands)	63	30	99	23
DECO BLUE SR HPR (Blue)	28	30	98	8
DECO GREEN SR HPR (Green)	32	41	98	8
DECO RED SR HPR (Red)	26	31	98	8
DECO YELLOW SR HPR (Yellow)	85	22	98	8
SAFETY AND SECURITY Series (Safety Window Film) These thicker films meet the most stringent standards for burglary resistance, blast mitigation, windborne debris, and basic safety glazing				
SCL SR PS2 (Clear)	89	16	95	10
SCL SR PS4 (Clear)	89	16	95	10
SCL SR PS7 (Clear)	88	16	95	10

EASTMAN

© Eastman Chemical Company 2014. LLumar ® and the LLumar ® logo are trademarks of Eastman Chemical Company or one of its subsidiaries. The ® used herein denotes registered trademark status in the US; marks referenced herein may also be registered internationally.

LLumar.com